

TYPICAL ROOM AND EQUIPMENT LAYOUT

(DASHED LINES DEPICT EQUIPMENT TRAVEL AND SERVICE CLEARANCES) RECOMMENDED FINISHED CEILING HEIGHT IS 9'-0"





GE Medical Systems

GE HISPEED ZXi **CT SCANNER**

GENERAL NOTES

- ALL SPECIFICATIONS AND SPACE REQUIREMENTS ARE SHOWN GENERICALLY.
 CONTACT GAMMA TECH, INC. FOR SPECIFIC REQUIREMENTS PERTAINING TO
 OPTIONAL EQUIPMENT COMPONENTS AND ADDITIONAL ROOM PREPARATION
- RECOMMENDED FINISHED CEILING HEIGHT IS 9'-0". MINIMUM FINISHED CEILING HEIGHT IS 7'-6".
- AMBIENT OPERATION TEMPERATURE: 68° TO 82° F. HUMIDITY: 30% TO 70% (NON-CONDENSING). ALLOWABLE TEMPERATURE CHANGE: 8°F PER HOUR ALLOWABLE HUMIDITY CHANGE: 5% PER HOUR

MAX - ALTITUDE: 8,200FT ABOVE SEA LEVEL

SCALE

 MAIN INCOMING POWER SUPPLY: 480VAC, THREE PHASE, 112.5KVA, DELTA OR WYE, 90AMP, 3 POLE, MAIN CB 5% VOLTAGE REGULATION, 90% POWER FACTOR

© PLANNING DIVISION

FILE NAME: GE HISPEED ZXI

REVISION DATE: 07.02.2008

EQUIPMENT SCHEDULE

	BTU / HOUR		W	/EIGHT	(LBS.)	
		DESCRIPTION	DIMENSIONS (IN.)			
1	16260	GENERAL ELECTRIC MEDICAL SYSTEMS HISPEED ZXI GANTRY	71.65	35.32	72.84	2580
2	318	GENERAL ELECTRIC MEDICAL SYSTEMS HISPEED ZXI PATIENT TABLE WITHOUT EXTENDED TABLE TOP	25.60	88.32	37.40	651
3	2911	GENERAL ELECTRIC MEDICAL SYSTEMS HISPEED ZXI OPERATOR'S CONSOLE / COMPUTER	43.31	33.90	51.90	449
4	615	GENERAL ELECTRIC MEDICAL SYSTEMS HISPEED ZXI POWER DISTRIBUTION UNIT	21.66	27.56	32.29	346

EQUIPMENT IDENTIFICATION NUMBER											
	BTU / HOUR			WEIGHT (LI							
		DESCRIPTION	DIMENSIONS								
1	16260	GENERAL ELECTRIC MEDICAL SYSTEMS HISPEED ZXI GANTRY	71.65	35.32							
2	318	GENERAL ELECTRIC MEDICAL SYSTEMS HISPEED ZXI PATIENT TABLE WITHOUT EXTENDED TABLE TOP	25.60	88.32							
3	2911	GENERAL ELECTRIC MEDICAL SYSTEMS HISPEED ZXI OPERATOR'S CONSOLE / COMPUTER	43.31	33.90							
4	615	GENERAL ELECTRIC MEDICAL SYSTEMS HISPEED ZXI POWER DISTRIBUTION UNIT	21.66	27.56							
		-	_								